

Semi Synthetic PLUS SAE 20W-50 Motor Oil

Petromerica Semi Synthetic PLUS SAE 20W-50 Motor Oil is a premium quality multi-grade motor oil designed with a state-of-the-art low friction additive system for superior engine protection even under the toughest driving conditions. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against performance robbing sludge and varnish deposits. Petromerica Semi Synthetic PLUS Motor Oil is recommended for passenger car, truck, sport utility vehicle and other mobile or stationary engines.

Petromerica Semi Synthetic PLUS SAE 20W-50 Motor Oil meets or exceeds American Petroleum Institute (API) SN PLUS service classification and is compatible with all prior API categories. Petromerica Semi Synthetic PLUS SAE 20W-50 Motor Oil has been field tested to be comparable to most American, Asian and European manufacturers' standards including ACEA A3/B3/B4, MB 229.1, GM 6094M and many other OEM's specifications where a semi synthetic API SN motor oil is recommended.

Benefits and Applications

- · Lower pour point reduces start-up wear during cold weather
- Enhanced oxidative stability, emission system and wear protection
- · Semi synthetic oil helps to improve fuel economy
- Superior resistance to sludge and varnish deposit formation

20W-50 Typical Characteristics - V190117

SAE GRADE	Syn Blend	20W-50
API SERVICE		SN PLUS
API Gravity	ASTM D4052-11	29.7
Flash Point, COC °C/°F	ASTM D92	206 / 402.8
Pour Point, °C/°F	ASTM D97	-30 / -22
Viscosity @ 40°C, cSt	ASTM D445	156.9
Viscosity @ 100°C, cSt	ASTM D445	18.6
Viscosity Index	ASTM D2270	133
CCS, mPa-sec °C max	ASTM D5293	9500 @ -15
Total Base No. TBN	ASTM D2896	7.9

Typical test data are average values only. Minor variations, which do not affect performance, may occur.

API SN PLUS

ACEA A3/B3/B4, MB 229.1, GM 6094M







Manufactured by US Global Petroleum, Franklin Park, IL 60131 - 773-376-9660

HANDLING AND SAFETY INFORMATION - Refer to USGLOBAL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information, data or products can be used without infringing patents of third parties.