

*Premium  
Performance*

# EVEREST™

**Everest Dextron®-VI Full Synthetic Automatic Transmission Fluid** is a licensed and GM® approved, high performance ATF fluid formulated from 100% synthetic base oils and an advanced additive package that meets or exceeds the performance, protection and service requirements of virtually all makes and models of passenger car and light truck automatic transmissions manufactured worldwide requiring a General Motors DEXRON®-VI or earlier generation DEXRON® fluid.

Everest Dextron®-VI Full Synthetic Automatic Transmission Fluid is particularly recommended for use in GM 6-speed automatic transmissions and is fully backwards compatible with older GM automatic transmissions and may be used as a fluid top-off, or for drain-and-fill or flush-and-fill installation or used in many power steering units and hydraulic systems. It provides extended life, superior performance, extreme protection, oxidation control, excellent low temperature and superior shear stability performance and offers consistent shift performance for the life of the fluid.

#### Approvals, Applications and Benefits

- GM DEXRON®, DEXRON® II, II-E, III, III-G, III-H, VI • Ford MERCON®, MERCON® LV • Acura ATF-Z1 • Audi 5 HP LT71141
- Chrysler (Mopar) ATF-Plus, ATF +3, ATF +4 • Allison C-3, C-4, TES-295, TES-389 • CAT TO-2 • Daewoo LT 71141 • Esso LT 71141
- BMW • Honda Z-1 • Hyundai/Kia SP-II/III/IV • JASO • FIAT T-IV type, JWS 3309 • Jaguar ATF 3403 M115, ATF LT71141, ZF 5HP24
- ISUZU BESCO ATF-II /III • Mazda ATF D-II/M-III/M-V/FZ/S-1/N-1 • MINI COOPER T-IV • Opel (all vehicles) • Peugeot ZF 4HP20
- Mercedes • Mitsubishi • Nissan/ Infinity Matic Fluids • Toyota ATF D-II/D-III/T-III/T-IV/WS • VW 5 HP, G-055-025 A2 (JWS 3309)
- Porsche ZF 5HP19FL, ZF 5HP20, LT71141 • Saab T-IV • Scion (all vehicles) • Shell 3403, M115, LA 2634 • Subaru ATF • Suzuki ATF
- Vickers M2950-S, I-286-S • Voith • Volvo CE 97340 • ZF all 3 & 4 speed transmission • and many more
- Superior all-temperature, year-round protection and high performance
- Advanced anti-wear protection and shear stability
- Smoother shifting, protection against shudder
- Extended life of service and performance

#### Typical Characteristics - Dextron® VI ATF V180301

GRADE	Test Method	DEXRON®-VI
Color	Visual	Red
Viscosity @ 100°C, cSt	ASTMD 445	5.8
Viscosity @ 40°C, cSt	ASTMD 445	29.5
Viscosity Index	ASTMD 2270	145
Pour Point, °C/°F	ASTMD 97	-51/ -59.8
Flash Point, COC °C/°F	ASTMD 92	220/ 428
API Gravity	ASTMD 1298	36.0
Brookfield Vis.cP @ -40°C	ASTMD 2983	10,000

Typical test data are average values only. Minor variations, which do not affect performance, may occur.  
You should consult your owner's manual to verify proper fluid recommendation for your particular vehicle.

**HANDLING AND SAFETY INFORMATION** - Refer to EVEREST (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

